



## STRUTTED INTERIOR HIGH SPEED FABRIC DOOR



**PERFECT FOR MANUFACTURING, FOOD AND BEVERAGE,  
COLD STORAGE, WAREHOUSE AND DISTRIBUTION FACILITIES**

- **Engineered for high cycles**
  - Springless design requires minimal interruption for maintenance
  - Direct-mounted gear drive minimizes wear and tear
  - Variable frequency drive eliminates sudden jolts from door start/stop
- **Strut design** allows for quick section replacement, while reducing curtain deflection under pressure
- **Low maintenance** breakaway design with impact detection and push button self-repair; plug and play wiring



INDUSTRY LEADING  
COMMERCIAL & INDUSTRIAL SOLUTIONS


# MODEL 992 STRUTTED INTERIOR HIGH SPEED FABRIC DOOR

Attributes	General specifications
Application	Interior
Maximum width	16'
Maximum height	15'
Opening speed	Up to 65"/sec
Closing speed	Up to 40"/sec
Break-away self reset	Yes
Pressure/wind resistance*	Up to 4.0 PSF or 76 MPH
Operational pressure **	Up to 2.5 PSF or 53 MPH
Wind strut	1" strut standard
Door panel	2 layers of PVC-coated polyester with 1 layer of polyester weave
Vision	20" high windows spaced evenly across width of door
Operation	Direct drive motor and gearbox system with a door stop device
Control	Variable frequency drive NEMA 4X cULus listed Onboard self diagnostic and service reminder Built-in padlockable field disconnect
Obstruction detection	Infrared sensors mounted in-plane to the door curtain at 18" and 50" - 54" from floor
Reversing safety edge	Wireless reversing edge
Electrical availability	120V AC 1PH; 230V AC 1PH; 230V AC 3PH; 460V AC 3PH; 575V AC 3PH
Warranty	5-Year Limited


\* Pressure/wind resistance value is the ultimate pressure tested at door width of 16'. The mph is determined in accordance to ASCE 7-10 EXP B.

\*\* Operational pressure value is the pressure tested up to 100,000 cycles at door width of 16'.

## Color options



Red



Blue



Gray



Black

Actual colors may vary from brochure due to fluctuation in the printing process.  
Always request a color sample from your Overhead Door Distributor for accurate color matching.



INDUSTRY LEADING  
COMMERCIAL & INDUSTRIAL SOLUTIONS



2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067

1-800-929-DOOR • sales@overheaddoor.com

www.OverheadDoor.com